



iPRD-DC 40r 1000PV modular surge arrester - 2P - 1000VDC with remote transfer

A9L16436

Discontinued on: 31 March 2022

① Discontinued

| Ν | V | ıa | I | n |
|---|---|----|---|---|
| | | | | |

| Range of product | Acti 9 |
|-----------------------------|---|
| Product name | Acti9 iPRD-DC |
| Device short name | iPRD-DC |
| Product or component type | Surge arrester with pluggable cartridge |
| Poles description | 2P |
| Output type | Contact (volt-free) |
| Signal contacts composition | 1 SD (1 C/O) |
| Surge arrester type | Electrical distribution network |

| Complementary | |
|---|--|
| Surge arrester class type | Type 2 |
| Surge arrester technology | MOV |
| [Ue] rated operational voltage | 1000 V +/- 10 % DC |
| [In] nominal discharge current | 15 kA |
| [Imax] maximum discharge current | 40 kA |
| [Ucpv] maximum continuous operating voltage | Differential mode: 1000 V L+/L- Common mode: 1000 V L+/PE Common mode: 1000 V L-/PE |
| Maximum [Up] voltage protection level | Common mode <3.9 kV type 2 L+/PE Common mode <3.9 kV type 2 L-/PE Differential mode <3.9 kV type 2 L+/L- |
| Disconnector device type | Integrated disconnector |
| Local signalling | White/red flag |
| Signalling circuit voltage | AC: 250 V 50/60 Hz |
| Signalling output current | 0.25 A |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 6 |
| Height | 81 mm |
| Width | 54 mm |

| Depth | 69 mm |
|-------------------------|---|
| Net weight | 400 g |
| Colour | White (RAL 9003) |
| Response time | <= 25 ns |
| Connections - terminals | Tunnel type terminal 2.525 mm² rigid Tunnel type terminal 2.516 mm² flexible Tunnel type terminal 2.516 mm² flexible with ferrule |
| Wire stripping length | 14 mm |
| Tightening torque | 3.5 N.m |

Environment

| Standards | UTE C 61740-51 EN 50539-11 |
|---------------------------------------|--|
| Product certifications | CE |
| IP degree of protection | IP40 on front face: IP20 on terminal: |
| IK degree of protection | IK03 |
| Relative humidity | 590 % |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -2560 °C |
| Ambient air temperature for storage | -4085 °C |

Offer Sustainability

EU RoHS Directive Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty 18 months

Recommended replacement(s)

A9L16436 is replaced by:





iPRD-DC 40r 1000PV modular surge arrester - 2P - 1000VDC - with remote transfert ${\it A9L40281}$