

Product data sheet

Specifications



Unica - 1 S.O. - 2P+E, shutters, FR - 2 m - red

MGU3.059.03SL

ⓘ Discontinued on: 30 May 2014

ⓘ Discontinued

Main

Range	Unica
Device application	Power supply
Product or component type	Socket-outlet
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Socket number	1
Outlet poles configuration	2P + E
Outlet standard	French
Outlet standard description	Pin earth

Complementary

Cover type	With shutter
Device mounting	Flush
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Red
Pilot light	LED
Connections - terminals	Screwless terminals
Cable cross section	0...4 mm ² - cable stiffness: flexible 0...4 mm ² - cable stiffness: rigid
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 U _n , cos phi = 0.6
Electrical durability	10000 cycles, cos phi = 0.8
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V

Material	ASA + PC: mechanism cover
Quantity per set	Set of 1 blister
Product certifications	FR.ME63.B02375 AC
Embedding depth	27 mm
Depth	37 mm
Width	45 mm
Height	45 mm

Environment

Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Oil Liquid soap Alcohol Bleach UV resistant Acetone Petrol Window-cleaning fluid

Packing Units

Package 1 Weight	79.000 g
Package 1 Height	33.500 mm
Package 1 Width	4.400 mm
Package 1 Length	13.600 mm

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)