

Product data sheet

Specifications



Unica - rocker switch - 1-way - 10 AX 250 VAC - 1 m - ivory

MGU3.101.25

! To be discontinued on: 31 December 2023

! To be discontinued

Main

| | |
|---------------------------|----------------------------|
| Range of product | Unica |
| Aesthetic name | Unica (standard aesthetic) |
| Product or component type | Switch |
| Device presentation | Mechanism |
| Technology type | Electromechanical |
| Switch function | 1-pole 1-way |
| Number of rocker | 1 |
| Device application | Light control |
| Provided equipment | Internal power connection |
| Colour tint | Ivory |

Complementary

| | |
|--------------------------------|-------------------------------------------------------------------------------|
| Rated current | 10 AX |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Electrical durability | 10000 cycles |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Minimum load breaking capacity | 200 operations 1.25 In and 1.1 Un, cos phi = 0.3 |
| Opening distance | > 3 mm |
| Actuator | Rocker |
| Number of modules | 1 module |
| Connections - terminals | Screwless terminals |
| Cable cross section | 0...2.5 mm ² rigid cable 0...2.5 mm ² flexible cable |
| Material | ASA + PC: mechanism cover |
| Fixing mode | Clip-in |

| | |
|---------------------------------------|---------------------------------------------|
| Width | 22.5 mm |
| Height | 45 mm |
| Depth | 34 mm |
| Embedding depth | 22 mm |
| Product weight | 0.0174 kg |
| Ambient air temperature for operation | 25...35 °C |
| Ambient air temperature for storage | 0...50 °C |
| Standards | EMC directive LV directive EN 60669-1 |

Environment

| | |
|------------------------------|-------------------------------------------------------------------------------------------------------|
| IP degree of protection | IP20 |
| IK degree of protection | IK01 |
| Environmental characteristic | Bleach Alcohol UV resistant Petrol Oil Acetone Liquid soap Window-cleaning fluid |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4 cm |
| Package 1 Width | 6.5 cm |
| Package 1 Length | 6.8 cm |
| Package 1 Weight | 22 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 4.4 cm |
| Package 2 Width | 13.6 cm |
| Package 2 Length | 33.5 cm |
| Package 2 Weight | 274 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 120 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 3775 kg |

Offer Sustainability

| | |
|--------------------------|-----------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant |

[EU RoHS Declaration](#)

| | |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Recommended replacement(s)