Product datasheet

Specifications



Unica - TV single shield socket female individual - white

MGU3.465.18

① Discontinued on: 13 April 2023

① Discontinued

Main

Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	TV socket
Device presentation	Mechanism
TV socket type	Individual
Colour tint	White

Complementary

TV connector	Female IEC 9.52 mm
Path attenuation	11 dB TV signal5862 MHz
DC current flow	No
Number per line	1
Number of modules	2 modules
Material	ASA + PC: mechanism cover
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Product weight	0.073 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	1535 °C
Ambient air temperature for storage	035 °C
Environmental characteristic	Bleach

UV resistant

	Alcohol Petrol Acetone Window-cleaning fluid Liquid soap	
Standards	EMC directive EN 50083-4 EN 50083-2 EN 50083-1	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	6.6 cm
Package 1 Length	6.6 cm
Package 1 Weight	58.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.6 cm
Package 2 Width	13.5 cm
Package 2 Length	33.2 cm
Package 2 Weight	642.0 g
Unit Type of Package 3	S01
Number of Units in Package 3	20
Package 3 Height	15.0 cm
Package 3 Width	15.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	1.487 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months

Recommended replacement(s)