

# Product data sheet

Specifications



Socket-outlet, Odace, mechanism with fixing frame, 2P + E, 16A, French, shutter, screwless terminals, matt, anthracite

S540059

## Main

Range of product	Odace
Product or component type	Socket-outlet
Device presentation	Mechanism with fixing frame
Socket number	1
Type of packing	Paint cover
Number of terminals per pole	2

## Complementary

Device mounting	Flush
Outlet poles configuration	2P + E
Cover type	With shutter
Outlet standard deviation	French
Fixing mode	By screws
Colour tint	Anthracite (RAL 7021)
Surface finish	Matt
Rated current	16 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50 Hz
Service life in cycles	5000 cycles
Electrical durability	5000 cycles
Connections - terminals	Screwless terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 4 mm <sup>2</sup> for rigid cable(s) 1 x 1.5...2 x 4 mm <sup>2</sup> for stranded cable(s) 1 x 1.5...2 x 4 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	12 mm
Material	ASA + PC: mechanism cover PBT (polybutylene terephthalate) GF30: support frame PC (polycarbonate) GF10 FR: casing
Height	71 mm

<b>Width</b>	71 mm
<b>Depth</b>	44 mm
<b>Embedding depth</b>	28 mm
<b>Net weight</b>	0.045 kg
<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

<b>Ambient air temperature for storage</b>	-5...50 °C
<b>Dielectric strength</b>	2000 V
<b>Ambient air temperature for operation</b>	5...35 °C
<b>Standards</b>	NF C 61-314
<b>Product certifications</b>	LCIE: NF 603415A NF
<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP21D

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	4.600 cm
<b>Package 1 Width</b>	7.200 cm
<b>Package 1 Length</b>	7.300 cm
<b>Package 1 Weight</b>	44.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	5.700 cm
<b>Package 2 Width</b>	18.000 cm
<b>Package 2 Length</b>	37.000 cm
<b>Package 2 Weight</b>	560.000 g
<b>Unit Type of Package 3</b>	S04
<b>Number of Units in Package 3</b>	120
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	40.000 cm
<b>Package 3 Length</b>	60.000 cm
<b>Package 3 Weight</b>	7.530 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>Cradle to Cradle</b>	Bronze

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Minimum percentage of recycled plastic content</b>	54

### Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

### Recommended replacement(s)