

# Product sheet



LEGRAND

2 wires CONNECTED KIT with 7" internal unit Wi-Fi connected, PLUG-IN power supply and wall mounted entrance panel

REF. 369430 | EAN. 3414971930858

[> Visit e-catalogue](#)

## Product characteristics

- Thanks to the Wi - Fi connection, it's possible to associate the video internal unit to the Door Entry EASYKIT app
- It's possible to manage the main video internal unit functions (receiving calls, opening the door lock, activating the entrance panel/scrolling, FWR updating and additional activations) from the app.
- The system can be expanded up to 3 traditional handsfree internal units.
- Camera integration: An external CCTV colour camera can be directly connected to the entrance panel. The system is fully interoperable with Netatmo cameras for greater security outside and inside the house
- Alimentation 230V

## Installation

- Ideal for villa, mono or bi-family house. The kit offers a complete solution for a VDE installation

## Usage

- The smartphone, connected to the internal monitor, becomes an additional virtual indoor unit

## Advantages

- Wi-Fi connection of the internal unit
- Simple installation and configuration

## Technical characteristics

With video	Yes
Number of indoor stations	1
Number of outdoor stations	1
Number of call buttons	2
Installation technique	Bus system
Mounting method indoor station	Surface mounted
Colour indoor station	Black
Mounting method outdoor station	Surface mounted
Material outdoor station	Aluminium
Colour outdoor station	Grey

Nominal voltage	100-240 V
Supply current	0-1 A
Frequency	50-60 Hz
Sound level	82 dB
Standby consumption	10 mA
Halogen free	Yes
Antimicrobial treatment	No
Cable nature for connection	Flexible or rigid
Cable section	0.1-2.5 mm <sup>2</sup>
Fitted with USB plug	Yes

Expandable to max. number of indoor stations	6
Expandable to max. number of outdoor stations	2
Picture system	PAL
Property picture system	Colour
Overhear protected	No
Can be connected to smartphone	Yes
Internal communication	Yes
Hands free	Yes
With day/night function	Yes
Opening angle camera	95 °
Zoom, pan/tilt function	No
With memory function	No
Screen diagonal	177.8 mm
Screen diagonal (inch)	7 inch
Manual adjustable camera	No
Label space/information surface	Yes
Hearing aid compatible	No
Suitable for disabled persons	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Power consumption	30 W
Width	215 mm
Height	140 mm
Depth	22.3 mm
Degree of impact strength (IK)	IK07
Degree of protection (IP)	IP30
Operating / setting temperature	-10-50 °C
Storage temperature	-25-70 °C
Voltage type	AC/DC

Fitted with rainproof plate protection	Yes
With complementary luminous signal	Yes
Mounting method	Supporting bracket
Vertical fixing center distance	25-85 mm
Horizontal fixing center distance	35-110 mm
Control mode	Wireless
Contains Batteries and/or Accumulator	No
Additional unit	Yes
Loudness setting	Yes
Addressable	Yes
Door entry system with mobile application	Yes
Number of ringtones	20
Remote opening of gate / Electric door opener	Yes
Screen resolution	Other
Screen brightness setting	Yes
Screen contrast setting	Yes
Memory video function	No
Camera type	Fixed
Max distance between internal and external unit	100 m
Communication rank type	Other
Connected object	Yes
Operating method	Wifi network
Application store for download	Google Play Store
Programming way	Smartphone apps
With voice command	No
Programmable	No
Interoperable connection Protocol	No
Connectable by Internet box	Yes
Application name	Door Entry
Product use function	Door entry systems

## Documentation

TECHNICAL DOCUMENTATION

CATALOGUE PAGE & OTHERS

 LE11336AC.pdf | PDF (9.4Mo)

 ex223001\_0846.pdf | PDF (0.09Mo)

## Agreements & Certificates

 Decl. UE RED-70 339 01 | (0.41Mo)

 LGKFIPNPBA | (0.4Mo)