

Product sheet



LEGRAND

1-way pushswitch 6A 1 module white europe

REF. 278030L | EAN. 3414971574359

No price to display

> [Visit e-catalogue](#)

Technical characteristics

Assembly arrangement	Modular device for domestic switching devices
Model	Single push button
Method of operation	Rocker
Number of contacts as normally closed contact	0
Number of contacts as normally open contact	1
Number of contacts as change-over contact	0
Number of rockers	1
Number of modules (module system)	1
Number of poles	1
Nominal voltage	250 V
Rated current	6 A
With lighting	No
Feedback-signal contact	No
Connection type	Push-in clamp
Mounting method	Flush-mounted
Type of fastening	Engage (snap)
Material	Plastic

RAL-number (similar)	9003
Transparent	No
Label space/information surface	No
Imprint	None
Suitable for degree of protection (IP)	IP31
Degree of impact strength (IK)	IK04
Device width	45 mm
Device height	22.5 mm
Device depth	36.3 mm
Min. depth of built-in installation box	40 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Built-in depth	24 mm
Operating / setting temperature	-5-35 °C
Storage temperature	-10-70 °C
Frequency	50-60 Hz
Terminal marking indication	Yes
Terminals capacity	2.5-2.5 mm ²

Material quality	Thermoplastic
Halogen free	Yes
Antimicrobial treatment	No
Surface protection	Untreated
Surface finishing	Glossy
Colour	White

Cable nature for connection	Flexible or rigid
Cable section	2.5-2.5 mm ²

Documentation

TECHNICAL DOCUMENTATION

 F03156FR-00.pdf | PDF (0.1Mo)


 F03156EN-00.pdf | PDF (0.09Mo)

CAD & Design specs / BIM

BIM-LEGRAND-MOSAIC-2023-ENGLISH.rvt | RVT (126.68Mo)

BIM-LEGRAND-MOSAIC-2023-FRANCAIS.rvt | RVT (128.48Mo)

CATALOGUE PAGE & OTHERS

 ex223001_1173.pdf | PDF (0.14Mo)

Agreements & Certificates

 OC / CB-FR_707532/M1 | (1.51Mo)

 AENOR-030/002540 | (0.34Mo)